

Espesor		LAMINADOS EN FRIO				LAMINADOS EN CALIENTE				
		1,000 x 2,000	1,220 x 2,440	1,220 x 3,000	1,500 x 3,000	1,000 x 2,000	1,025 x 2,000	1,245 x 2,440	1,245 x 3,000	1,500 x 3,000
B.W.G.	mm.									
29	0.30	4.71	7.01	8.62	10.60					
28	0.35	5.50	8.18	10.06	12.36					
27	0.40	6.28	9.35	11.49	14.13					
26	0.45	7.07	10.52	12.93	15.90					
25	0.50	7.85	11.68	14.37	17.66					
24	0.55	8.64	12.85	15.80	19.43					
	0.60	9.42	14.02	17.24	21.20					
23	0.65	10.21	15.19	18.68	22.96					
22	0.70	10.99	16.36	20.11	24.73					
21	0.80	12.56	18.69	22.98	28.26					
20	0.90	14.13	21.03	25.86	31.79					
	1.00	15.70	23.37	28.73	35.33					
19	1.10	17.27	25.70	31.60	38.86					
18	1.25	19.63	29.21	35.91	44.16					
17	1.50	23.55	35.05	43.10	52.99					
16	1.60	25.12	37.39	45.97	56.52	25.12	25.75	38.15	46.91	56.52
15	1.80	28.26	42.06	51.72	63.59	28.26	28.97	42.92	52.78	63.59
14	2.00	31.40	46.74	57.46	70.65	31.40	32.19	47.69	58.64	70.65
13	2.25	35.33	52.58	64.64	79.48	35.33	36.21	53.66	65.97	79.48
12	2.50	39.25	58.42	71.83	88.31	39.25	40.23	59.62	73.30	88.31
	2.85	44.75	66.60	81.88	100.68	44.75	45.86	67.96	83.56	100.68
	3.00	47.11	70.12	86.21	105.99	47.11	48.29	71.55	87.97	105.99
1/8"	3.20					50.24	51.50	76.31	93.82	113.04
10	3.40					53.38	54.71	81.08	99.69	120.11
	3.55					55.74	57.13	84.66	104.09	125.40
	4.00					62.80	64.37	95.39	117.28	141.30
3/16"	4.75					74.58	76.44	113.27	139.27	167.79
	5.15					80.86	82.88	122.81	151.00	181.92
1/4"	6.35					99.70	102.19	151.43	186.18	224.31
5/16"	8.00					125.60	128.74	190.77	234.56	282.60
3/8"	9.50					149.15	152.88	226.54	278.54	335.59
	12.50					196.25	201.16	298.08	366.50	441.56

Calidad de Acero LAF IRAM IAS U 500 05

Calidad de Acero LAC IRAM IAS U 500 231

Peso Específico utilizado:	7.85
----------------------------	------